

Features :

- 0.98 typical of power factor
- High reliability and low ripple noise
- Built-in remote sense function
- Built-in remote ON/OFF control
- Built-in power good signal output
- Programmable output voltage
- Forced current sharing at parallel operation
- Output short circuit / over voltage / overload / over temperature protections
- CB, CE, UL, TUV approved



MODEL		800S-P009	800S-P012	800S-P015	800S-P018	800S-P024	800S-P036	800S-P048	800S-P060	
Output	DC Voltage	9V	12V	15V	18V	24V	36V	48V	60V	
	Rated Current	88A	66A	53A	44.4A	33A	22.2A	16A	13A	
	Rated Power	792W	792W	795W	800W	792W	800W	768W	780W	
	Ripple & Noise (max.)	150mVp-p	150mVp-p	150mVp-p	180mVp-p	240mVp-p	360mVp-p	480mVp-p	600mVp-p	
	Voltage Adj. Range	+3%~12% typical adjustment by potentiometer; 20% ~ 100% adjustment by 1~ 5VDC external control								
	Line & Load Regulation	Less than 1%								
	Setup, Rise, Hold Time	800ms, 400ms, 12ms at full load								
Input	Voltage Range	180 ~ 260VAC / 260 ~ 370VAC								
	frequency Range	47 ~ 63Hz								
	Power Factor (Typ.)	0.98 / 230VAC								
	Efficiency (Typ.)	83%	84%	85%	86%	88%	88%	89%	90%	
	AC Current (Typ.)	4.5A / 230VAC								
	Inrush current (Typ.)	60A / 230VAC								
Protection	Leakage Current (max.)	< 3.5mA / 240VAC								
	Over Load	105 ~ 115% rated output power (Current limiting, delay shut down output voltage, re-power on to recover)								
	Over Voltage	110 ~ 135% follow to output set up point(shut down output voltage, re-power on to recover)								
Environment	Over Temperature	>100°C / measure by heat sink, near transformer (shut down output voltage,recovers automatically after temperature goes down)								
	Working Temp. & Humidity	0 ~ +50°C; 20% ~ 90% RH non-condensing								
	Storage Temp.& Humidity	-20 ~ +85°C, / 10 ~95%RH								
Safety & EMC	Temp.Coefficint	±0.04% / °C (0 ~ 50°C)								
	Safety Standards	UL1950, TUV EN60950-1 Approved								
	Withstand Voltage	I/P - O/P : 3KVAC; I/P - FG :1.5KVAC; O/P - FG : 0.5KVAC								
	Isolation Resistance	I/P - O/P, I/P - FG, O/P - FG : 100M Ohms / 500VDC								
	EMI Conduction & Radiation	Compliance to EN55022 (CISPR22) class A								
	Harmonic Current	Compliance to EN61000-3-2,3								
Others	EMS Immunity	Compliance to EN55024								
	Power Good Signal	Open collector NPN transistor								
	Special Function	DC voltage adj.,Remote sensing, Remote control, Parallel operation								
	Cooling	Power rating and temperature controlled cooling fan								
	MTBF	74.9K Hrs min. MIL-HDBK-217F(25°C)								
	Dimension (L*W*H)(mm)	291x120x67.5								
Packing	2.3kg ; 8sets / 22kgs / Carton									