



# CFM10/15

S E R I E S

## 10/15 WATT OPEN FRAME AC-DC MODULES



### Features

- Universal Input Range 85-264VAC
- Efficiency to 82%
- Meets EN55022 Class B
- Continuous Short Circuit Protection
- Leakage Current 0.25mA Max.
- PCB Mountable

### CFM10 Series

MODEL	OUTPUT VOLTAGE	MAX. LOAD	MIN. LOAD	RIPPLE & NOISE	VOLTAGE ACCURACY	LINE REGULATION	LOAD REGULATION	%EFF
CFM1001S	5 V	2000mA	0A	1%	± 1%	± 0.5%	± 1%	73% Typ.
CFM1002S	12 V	840mA	0A	1%	± 1%	± 0.5%	± 1%	76% Typ.
CFM1003S	15 V	670mA	0A	1%	± 1%	± 0.5%	± 1%	76% Typ.
CFM1005S	24 V	420mA	0A	1%	± 1%	± 0.5%	± 1%	77% Typ.
CFM1007S	3.3 V	2500mA	0A	50mV	± 1%	± 0.5%	± 1%	67% Typ.
CFM1009S	9 V	1120mA	0A	1%	± 1%	± 0.5%	± 1%	73% Typ.

### CFM15 Series

MODEL	OUTPUT VOLTAGE	MAX. LOAD	MIN. LOAD	RIPPLE & NOISE	VOLTAGE ACCURACY	LINE REGULATION	LOAD REGULATION	%EFF
CFM1501S	5 V	3000mA	0A	1%	± 1%	± 0.5%	± 1%	74% Typ.
CFM1502S	12 V	1250mA	0A	1%	± 1%	± 0.5%	± 1%	80% Typ.
CFM1503S	15 V	1000mA	0A	1%	± 1%	± 0.5%	± 1%	81% Typ.
CFM1505S	24 V	630mA	0A	1%	± 1%	± 0.5%	± 1%	83% Typ.
CFM1507S	3.3 V	3000mA	0A	50mV	± 1%	± 0.5%	± 1%	69% Typ.
CFM1509S	9 V	1670mA	0A	1%	± 1%	± 0.5%	± 1%	76% Typ.

