



65 Watt Series

Small Size Desktop Type

Level VI

ATS065S - P X X X

P : C6 ← → O / P Voltage

Green Mode

CEC , DoE Level VI , Energy Star , ErP Stage 2 , NRCAN
NO Load Power Consumption Less Than 0.21W

Features :

- Smaller size of 108 x 46 x 32mm
- 100-240VAC Universal Input
- Single Output to 65W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 1 Year Warranty

Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / LPS

Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	3.5mA @ 3 Pin
Efficiency	DoE Level VI , Energy Star , ErP Stage 2 & NRCAN Certified
EMI Conduction & Radiation	Compliance to EN55022 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to IEC61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Model	O/P Voltage	O/P Current	Watt
ATS065S-P150	15.0V	4.34A	65W
ATS065S-P160	16.0V	4.07A	65W
ATS065S-P180	18.0V	3.62A	65W
ATS065S-P185	18.5V	3.52A	65W
ATS065S-P190	19.0V	3.43A	65W
ATS065S-P200	20.0V	3.25A	65W
ATS065S-P240	24.0V	2.71A	65W

Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1.4A Max.
Protection	Internal Primary Current Fuse , Inrush Limiting
Configuration	IEC60320/C6

Output

Load Regulation	±5% (Typical)
Ripple	1 ~ 2% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	18AWG / 16AWG
Ferrite Core	No(Optional)

Mechanical

Case Dimension	L 108 x W 46 x H 32 (mm)
Weight	248 g (Ref.)

